

# JFS 12



## General Specifications

Custom 2-Color Paint (pump only)	
Water Pump	Rust proof hydraulic power 20bar (290psi)
Water Tank (standard)	158 G (600 L)
Wire Remote Control	35 M (130')
Auto Lube System	Hopper Only
Hopper Vibrator	Standard
Tool Box	Standard

Alliance Concrete Pumps Inc. reserves the right to make changes to these specifications.

Other Chassis available contact your sales representative.

## Pump Specifications

Output	Rod Side	115 m <sup>3</sup> /h (150 yd <sup>3</sup> /h)
	Piston Side	72 m <sup>3</sup> /h (94 yd <sup>3</sup> /h)
Pressure	Rod Side	92 Bar (1334 psi)
	Piston Side	148 bar (2146 psi)
Max. Aggregate Size	63 mm (2.5")	
S-Tube Size	8" X 7"	
Hard Chromed Concrete Cylinder	200 mm X 1400 mm (8" X 55")	
Main Oil Pump	Rexroth hydromatic A4VSO250	
Lube System (Hopper)	Automatic	
All Hydraulic Switching System (with manual overrides)		
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	29	
Outrigger Front & Rear	Vertical Extension	

These are theoretical values and may change depending on conditions of the concrete mixes.



**Head Office** 26162 30A Ave Aldergrove, BC V4W 2W5  
TF 888.870.0908 P 604-607-0908 F 604.607.0903

**USA Office** Unit 101-4440 Township Line Rd. Skippack, PA 19474 USA  
TF 888.584.7231 P 610.584.7231 F 610.584.7251